Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON


Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical


Round Luminaire	Diam. 870 mm	Height	205 mm
Round Luminous Area	Diam. 870 mm	Height	205 mm
Horizontal Luminous Area	0.594468 m2	Emitting area on Plane 180°	0.178350 m2
Emitting area on Plane 0°	0.178350 m2	Emitting area on Plane 270°	0.178350 m2
Emitting area on Plane 90°	0.178350 m2	Glare area at 76°	0.316867 m2
Coordinate system	CG	Symmetry Type	Double Symmetrical
Date	22-09-2022	Maximum Gamma Angle	180
Measurement Distance	6.44	Measurement Flux	6723.33 lm
Operator	ASSELUM	Rated Voltage	37.57 V
Temperature	25.00 °C	Rated Current	1.40 A
Humidity	46.30 %	Photocell	Czibula Grundmann
Notes	RM22071402.2		

Luminaire Sources

Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
	2835 LM281B+PRO (VK)	SAMSUNG	6723.32	52.65	1

C.I.E.	48 79 95 84 100	D DIN 5040	B31
F UTE	0.84 E + 0.16 T	B NBN	BZ 4 / 3 / BZ 5





Semiplanos C
180.0 — 0.0
270.0 — 90.0

ULOR 15.96 %
DLOR 84.04 %
RN 15.96 %

Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON

Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical


Luminous Intensity Table cd **Table 1/1**

	C 0.00	C 15.00	C 30.00	C 45.00	C 60.00	C 75.00	C 90.00
G 0.0	2134.97	2134.97	2134.97	2134.97	2134.97	2134.97	2134.97
G 2.5	2130.65	2131.16	2131.58	2131.75	2131.56	2131.23	2131.06
G 5.0	2121.12	2121.76	2122.24	2122.48	2122.42	2122.23	2122.11
G 7.5	2106.72	2107.22	2107.59	2107.98	2108.48	2108.92	2109.12
G 10.0	2086.43	2086.91	2087.26	2087.81	2088.75	2089.70	2090.14
G 12.5	2059.65	2060.00	2060.11	2060.50	2061.49	2062.59	2063.11
G 15.0	2026.00	2026.62	2026.74	2026.84	2027.29	2027.84	2028.11
G 17.5	1986.90	1987.30	1987.05	1986.84	1987.18	1987.75	1988.05
G 20.0	1941.91	1942.54	1942.32	1942.17	1942.74	1943.60	1944.04
G 22.5	1891.47	1892.63	1892.99	1893.18	1893.65	1894.20	1894.47
G 25.0	1836.91	1845.16	1852.37	1854.94	1850.81	1844.14	1840.65
G 27.5	1790.27	1784.87	1776.82	1775.38	1786.33	1801.48	1809.13
G 30.0	1712.58	1711.78	1709.22	1706.99	1706.59	1707.29	1707.81
G 32.5	1643.34	1642.46	1640.27	1639.77	1642.88	1647.26	1649.48
G 35.0	1565.59	1570.62	1574.27	1574.82	1571.42	1566.77	1564.43
G 37.5	1421.02	1433.18	1437.22	1439.23	1443.72	1448.89	1451.36
G 40.0	1427.24	1429.84	1431.25	1432.30	1433.59	1434.79	1435.32
G 42.5	1354.20	1355.77	1357.98	1361.06	1364.93	1368.37	1369.85
G 45.0	1279.53	1279.52	1279.54	1281.47	1286.34	1291.70	1294.22
G 47.5	1201.27	1202.89	1204.51	1206.45	1208.82	1210.90	1211.80
G 50.0	1121.81	1123.71	1126.17	1129.07	1132.18	1134.73	1135.78
G 52.5	1045.68	1047.33	1048.67	1050.39	1052.88	1055.25	1056.31
G 55.0	965.94	967.57	969.13	970.90	973.01	974.84	975.63
G 57.5	889.82	891.66	892.64	893.30	894.02	894.65	894.92
G 60.0	811.60	812.41	812.75	813.28	814.44	815.69	816.28
G 62.5	734.70	735.53	735.63	735.91	737.01	738.32	738.95
G 65.0	658.92	660.05	660.73	661.00	660.97	660.80	660.70
G 67.5	583.48	583.85	583.66	583.82	584.91	586.26	586.93
G 70.0	510.69	511.81	512.44	512.09	510.55	508.75	507.88
G 72.5	438.23	439.95	440.91	440.72	439.29	437.54	436.69
G 75.0	369.70	371.35	372.14	371.88	370.60	369.11	368.38
G 77.5	302.78	304.09	304.94	305.04	304.28	303.25	302.73
G 80.0	239.55	241.47	242.67	242.70	241.42	239.75	238.93
G 82.5	181.21	182.52	183.24	183.15	182.19	181.02	180.44
G 85.0	126.94	128.36	129.07	128.89	127.84	126.58	125.98
G 87.5	80.32	84.23	87.72	88.81	86.34	82.57	80.62
G 90.0	62.54	64.73	67.02	67.70	65.74	62.83	61.33
G 92.5	65.98	67.45	68.62	68.58	67.25	65.20	64.15
G 95.0	79.75	78.70	77.79	77.03	76.41	75.99	75.84
G 97.5	94.99	93.34	91.39	89.93	89.49	89.68	89.89
G100.0	104.26	103.00	101.57	100.15	98.92	98.06	97.74
G102.5	114.95	112.98	110.65	108.88	108.33	108.54	108.78
G105.0	122.75	122.09	121.12	120.00	118.93	118.12	117.80
G107.5	134.79	133.35	131.53	130.01	129.27	129.09	129.12
G110.0	146.62	145.26	143.72	142.59	142.25	142.40	142.56
G112.5	158.54	157.78	156.68	155.64	154.95	154.61	154.52
G115.0	172.00	172.48	172.55	171.49	168.94	166.19	164.91
G117.5	186.70	187.06	187.03	185.94	183.48	180.86	179.64
G120.0	197.01	198.06	198.86	198.20	195.45	192.20	190.63
G122.5	203.20	204.71	206.07	205.85	203.27	200.02	198.42
G125.0	208.27	210.55	212.35	212.36	209.84	206.44	204.74
G127.5	211.75	214.52	216.84	217.30	214.89	211.45	209.69
G130.0	213.17	216.26	219.41	220.45	218.11	214.51	212.64
G132.5	213.08	216.57	220.30	221.89	219.90	216.47	214.65
G135.0	212.61	216.12	219.95	221.78	220.17	217.10	215.44
G137.5	210.78	214.38	218.41	220.63	219.62	217.14	215.74
G140.0	208.75	212.33	216.40	218.83	218.00	216.17	215.06
G142.5	206.98	210.40	214.40	216.96	216.52	215.05	214.10
G145.0	206.74	209.82	213.61	216.21	216.35	215.15	214.37
G147.5	208.12	210.14	213.12	215.56	216.06	215.97	215.83
G150.0	210.30	211.12	212.85	214.81	216.64	217.93	218.41
G152.5	212.53	212.44	213.32	215.13	217.67	220.00	221.02
G155.0	220.50	219.15	219.13	220.60	223.41	226.26	227.57
G157.5	230.76	229.64	230.42	232.65	235.73	238.52	239.74
G160.0	240.07	239.24	240.30	243.00	246.89	250.49	252.07
G162.5	246.71	246.52	247.80	250.24	253.39	256.18	257.38
G165.0	251.32	250.98	251.80	253.69	256.38	258.86	259.95
G167.5	256.61	255.64	255.41	256.23	258.12	260.14	261.08
G170.0	259.05	258.57	258.36	258.44	258.86	259.29	259.49
G172.5	261.36	260.49	259.83	259.47	259.53	259.67	259.75
G175.0	263.26	262.22	261.26	260.62	260.46	260.57	260.67
G177.5	264.73	263.69	262.66	261.88	261.52	261.44	261.46
G180.0	262.98	262.98	262.98	262.98	262.98	262.98	262.98

Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON


Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

Diam=870mm



Semiplanos C


180.0 0.0
270.0 90.0



Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON


Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

Diam=870mm



Semiplanos C





Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON

Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Working Plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions	Lateral View					Viewed Endwise				
x=2H y=2H	13.9	15.0	14.4	15.5	16.1	14.0	15.1	14.5	15.6	16.1
x=2H y=3H	15.2	16.2	15.7	16.7	17.3	15.2	16.2	15.7	16.7	17.3
x=2H y=4H	15.6	16.6	16.2	17.1	17.7	15.7	16.6	16.2	17.1	17.7
x=2H y=6H	15.9	16.8	16.5	17.4	18.0	16.0	16.8	16.5	17.4	18.0
x=2H y=8H	16.0	16.9	16.6	17.4	18.1	16.0	16.9	16.6	17.4	18.1
x=2H y=12H	16.1	16.9	16.7	17.4	18.1	16.1	16.9	16.7	17.4	18.1
x=4H y=2H	14.4	15.4	15.0	15.9	16.5	14.5	15.4	15.0	15.9	16.5
x=4H y=3H	15.9	16.7	16.5	17.2	17.9	15.9	16.7	16.5	17.2	17.9
x=4H y=4H	16.4	17.2	17.1	17.7	18.4	16.5	17.2	17.1	17.8	18.4
x=4H y=6H	16.9	17.5	17.5	18.1	18.8	16.9	17.5	17.5	18.1	18.8
x=4H y=8H	17.0	17.5	17.7	18.2	18.9	17.0	17.5	17.7	18.2	18.9
x=4H y=12H	17.1	17.6	17.7	18.2	19.0	17.1	17.6	17.7	18.2	19.0
x=8H y=4H	16.6	17.2	17.3	17.8	18.6	16.6	17.2	17.3	17.8	18.6
x=8H y=6H	17.2	17.6	17.9	18.3	19.1	17.2	17.6	17.9	18.3	19.1
x=8H y=8H	17.4	17.8	18.1	18.5	19.3	17.4	17.8	18.1	18.5	19.3
x=8H y=12H	17.5	17.8	18.2	18.6	19.4	17.5	17.8	18.2	18.6	19.4
x=12H y=4H	16.9	17.5	17.6	18.1	18.9	17.0	17.5	17.6	18.1	18.9
x=12H y=6H	17.5	17.9	18.2	18.6	19.4	17.5	17.9	18.2	18.6	19.4
x=12H y=8H	17.7	18.0	18.4	18.7	19.5	17.7	18.0	18.4	18.7	19.5

Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON


Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.27	2.54	3.81	5.08	6.35	OC	1.29	2.57	3.86	5.15	6.44
OB	1.27	2.54	3.81	5.08	6.35	OD	1.29	2.57	3.86	5.15	6.44

Luminous Intensities [cd]

	0	5	15	25	35	45	55	65	75	85
OA	2134.97	2121.12	2026.00	1836.91	1565.59	1279.53	965.94	658.92	369.70	126.94
OB	2134.97	2121.12	2026.00	1836.91	1565.59	1279.53	965.94	658.92	369.70	126.94
OC	2134.97	2122.11	2028.11	1840.65	1564.43	1294.22	975.63	660.70	368.38	125.98
OD	2134.97	2122.11	2028.11	1840.65	1564.43	1294.22	975.63	660.70	368.38	125.98



H[m]	D[m]	Max lux	Med lux	Alpha=51.8°+51.8° G=0.0
1.00	2.54	2135	607	
2.00	5.08	534	152	
3.00	7.62	237	67	
4.00	10.16	133	38	
5.00	12.70	85	24	

H[m]	D[m]	Max lux	Med lux	Beta=52.2°+52.2° G=0.0
1.00	2.57	2135	607	
2.00	5.15	534	152	
3.00	7.72	237	67	
4.00	10.30	133	38	
5.00	12.87	85	24	

Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON

Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

Flujo Total=6723.32 Flujo Luminaria=6723.32


RI	0.60	0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	10.00	20.00
DRR	0.32	0.40	0.47	0.54	0.60	0.68	0.74	0.78	0.83	0.86	0.92	0.96
RC	5	5	5	5	5	5	5	5	5	5	5	5

Flujo Zonal por 1000 Lúmenes

Y°	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
ZF(Y)	30	115	241	386	533	662	760	818	840	853	872	897	925	950	970	986	996	1000

Códigos de Flujo C.I.E.
48 79 95 84 100

C.I.E.	5	LOR	100.00000 %
D DIN 5040	B31	ULOR	15.96005 %
F UTE	0.84 E + 0.16 T	DLOR	84.03995 %
B NBN	BZ 4 / 3 / BZ 5	UFF	15.96005 %
RN	15.96005 %	DFF	84.03995 %
BLF	1.0	FFR	18.99102 %



Flujo Zonal				
Gamma °	Flujo	Suma lm	Flujo [%]	Suma [%]
0°	0.00	0.00	0.00%	0.00 %
5°	7.57	7.57	0.76 %	0.76 %
10°	22.40	29.97	2.24 %	3.00 %
15°	36.31	66.28	3.63 %	6.63 %
20°	48.65	114.94	4.87 %	11.49 %
25°	59.06	174.00	5.91 %	17.40 %
30°	67.06	241.06	6.71 %	24.11 %
35°	71.85	312.91	7.18 %	31.29 %
40°	72.94	385.84	7.29 %	38.58 %
45°	74.86	460.70	7.49 %	46.07 %
50°	72.49	533.18	7.25 %	53.32 %
55°	67.90	601.09	6.79 %	60.11 %
60°	61.35	662.43	6.13 %	66.24 %
65°	53.25	715.69	5.33 %	71.57 %
70°	44.05	759.74	4.40 %	75.97 %
75°	34.20	793.93	3.42 %	79.39 %
80°	24.26	818.20	2.43 %	81.82 %
85°	14.81	833.01	1.48 %	83.30 %
90°	7.39	840.40	0.74 %	84.04 %
95°	5.63	846.03	0.56 %	84.60 %
100°	7.27	853.30	0.73 %	85.33 %
105°	8.77	862.07	0.88 %	86.21 %
110°	10.21	872.28	1.02 %	87.23 %
115°	11.77	884.05	1.18 %	88.41 %
120°	13.29	897.34	1.33 %	89.73 %
125°	13.97	911.31	1.40 %	91.13 %
130°	13.83	925.13	1.38 %	92.51 %
135°	13.10	938.23	1.31 %	93.82 %
140°	11.96	950.18	1.20 %	95.02 %
145°	10.64	960.82	1.06 %	96.08 %
150°	9.37	970.19	0.94 %	97.02 %
155°	8.17	978.36	0.82 %	97.84 %
160°	7.27	985.64	0.73 %	98.56 %
165°	6.13	991.77	0.61 %	99.18 %
170°	4.53	996.30	0.45 %	99.63 %
175°	2.77	999.07	0.28 %	99.91 %
180°	0.93	1000.00	0.09 %	100.00 %

Luminaire
Code 24902xxx190
Name PLAFONET 95 LED CREAM RIBBON
Measurem.
Code CL092A22F019GE1
Name PLAFONET 95 LED CREAM RIBBON

Luminaire Flux	6723.32 lm	Luminaire Power	52.65 W	Efficacy	127.70 lm/W	Efficiency	100.00%
Sources Flux	6723.32 lm	Maximum value	2134.97 cd	Position	C=0.00 G=0.00	CG	Double Symmetrical

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=2.50m

